

2D BARCODE SCANNER

OMNI 8800

Performance	Image Sensor		1280*800 Cmos Sensor	
	Illumination		Red LED	
	Symbologies	2D		(PDF417)、(Micro PDF417)、(QR Code)、(Micro QR)、(Data Matrix)、(Aztec)、
		1D		(Codabar)、(Code 39)、(Code 32)、(Industrial 2 of 5)、(Interleaved 2 of 5)、GS1-128、(Matrix 2 of 5)、(Code 93)、(Code 11)、(Code 128)、(MSI plessey)、(UPC-A)、(UPC-E)、(EAN/JAN-8)、(EAN/JAN-13)、(GS1 DataBar(RSS14)GS1 DataBar Limited、GS1 DataBar Expanded
	Resolution*		≥5mil	
	Decode Range*	EAN-13 (13mil)		0mm~280mm (Barcode Size: 31mm*7mm)
		Code39 (5mil)		0mm~120mm (Barcode Size: 11mm*6mm)
		Data Matrix (10mil)		0mm~130mm (Barcode Size: 5mm*5mm)
		QR Code (15mil)		0mm~170mm (Barcode Size: 10mm*10mm)
	Min Print Contract*		≥20%	
	Scan Angle**		Skew±55°, Pitch±50°, Roll 360°	
	FOV		Horizontal 46°, Vertical 30°	
	Electronic	Interface		USB、USB-CDC、RS232
		Dimension(mm)		163.5 (W)×76.7(D)×164.4(H)(Max)
Net Weight			549G	
Indicators			Beeper, LED Indicator	
Voltage			5VDC	
Power			1.25W(Typical)	
Current@5 VDC		Operating		250mA(RMS Typical), 420mA(RMS Max)
		Standby		150mA
Environmental	Operating Temperature		0°C~+60°C	
	Storage Temperature		-40°C~+70°C	
	Humidity		5%~95% (Non-Condensing)	
Accessories	Cable		USB Cable / RS 232 Cable	